



MASSEY FERGUSON

75 - 86 HP
55 - 63 kW

MF 3300



FROM MASSEY FERGUSON

Good at everything, all the time

All the time by your side, for your production to go-ahead

The new Massey Ferguson 3300 series is based on the heritage of the popular, robust and reliable MF 400 Xtra Narrow tractor models. While the front axle, transmission and rear linkage are almost identical to the MF 435 Xtra and MF 440 Xtra narrow-width tractors, the MF 3300 Series features a brand-new AGCO Power electronic engine, which makes your agricultural production simpler, more powerful and more reliable.

The Massey Ferguson 3300 is aimed at specialist farming operations, which includes fruit, nut and seed production. In addition, the MF 3300 is also ideal for horticultural applications.

The technology incorporated in the MF 3300 not only makes it highly affordable, but extremely competitive in terms of specification

The MF 3300 Series is available in an open station and cab model, and in 2WD and 4WD



AGCO Power Engine

Efficient and powerful

The MF 3300 series of compact tractors are equipped with the 3-cylinder AGCO Power Engine. The engine features a common rail with an electronic control unit (ECU) to monitor all fuel and air parameters, which makes your agricultural production simpler, more powerful and more reliable. The ECU is coupled with a mini dashboard computer providing a real-time readout of hourly fuel consumption.

An engine memory function means that, at the press of a button, a preset engine revolution can be engaged, which translates into a more consistent application and less wear-and-tear on the drive-line, linkage and implements.

The engine has been optimized for lower emissions and fuel economy.

Mechanical synchromesh transmission

The right transmission for your needs

A straightforward Mechanical synchromesh transmission (12F x 4R) makes all work possible for the MF 3300. Optional creeper (18F x 4R) mounted between the gearbox and rear axle make it possible to achieve a speed of 500 m/h.



Hydraulic System

A simple open-centre hydraulic system is powered by two gear pumps on the MF 3300 series. The 17 litres/min pump provides all the internal services, while the 42 litres/min pump allows the rear linkage to lift 2,100kg.

Two hydraulic remote valves flow-rate sum of 59 litres per minute oil flow or 180 bar pressure, making it ideal for grounds care and other farm maintenance work.

Independent Power Take-off (IPTO)

All models are equipped with an independent hydraulically engaged 540 rpm PTO with 2 discs split torque clutch. Power transmission to the PTO is fixed and its engagement and disengagement is done by a wet clutch. This allows drive to be transferred to rear-mounted implements such as sprayers, mowers, threshing machines, keeping maintenance and fuel consumption to minimum.

Heavy Duty Drawbar

Essential for using trailed equipment. The heavy duty drawbar is designed to work with heavy implements. It is the best for haulage work and spraying.



Your Workplace

The MF 3300 Series is available in an open station and cab model

This compact and strong tractor, is narrow enough to pass between plants without risk of damage. The operator environment provides comfort and ease of use during long working hours, often in extreme weather conditions.

The cab is designed for maximum visibility and safety with easy access controls that are very simple to operate efficiently. Comfort is ensured with air-conditioning as standard, and incoming air passes through a cab air filter.



Specifications

	MF 3307	MF3308
Version	Platform/Cab	Platform/Cab
Engine Performance		
Engine Power	ISO hp (kW) 75 (55)	86 (63)
Max Torque	Nm @1500 rpm 278	307
Rated engine speed	2,200	2,200
Engine		
Engine type / no. of Cylinders /Capacity / Aspiration	AGCO Power 33 CWC13 / 3 / 3300cc / Turbocharged	
Injection	Common Rail	
Transmission		
12 x 4 Synchronized	●	
18 x 4 synchronized Creeper	○	
Power take-off		
Type	Split Torque, Independent Hydraulic Engagement	
Activation	Lever-operated	
Speed	540 @ 1900 rpm	
Steering		
Hydrostatic	●	
Hydraulic Pump	31	
Hydraulics		
Oil Flow	Litre/min 59	
Pressure	bar 180	
Remote Control Valves	2	
Maximum Lift Capacity	2'100	
Gauges		
Front gauge (minimum / maximum)	mm 1'180 - 1'513 (2WD)	
	mm 1'190 - 1'310 (4WD)	
Rear gauge (minimum / maximum)	mm 966 - 1.300	
Brakes		
Activation / Type	Mechanical / Wet Disc	
Standard wheels and tyres		
4x2	Front 7.50-16	7.50-16
	Rear 14.9x24	16.9x24
4x4	Front 250/80-18	250/80-18
	Rear 14.9x24	16.9x24
Capacities		
Fuel tank	Litres 85	

● Standard ○ Optional

Dimensions (Rops/Cab)



A	Length	mm	3'765
B	Wheelbase	mm	2'300
C	Maximum Height (Rops Tilted/Rops/Cab)	mm	1'609 / 2'327 / 2'356
D	Ground Clearance	mm	300



E	Front outer width	mm	1'406
F	Rear outer width	mm	1'406 / 1'274

Unladen Weight

2WD Rops	MF 3307/MF3308	kgs	2'755
Rops	MF 3307/MF3308	kgs	2'900
Cab	MF 3307/MF3308	kgs	3'046



MF 3300



MASSEY FERGUSON



Web: masseyferguson.com/en_za/

Facebook: www.facebook.com/MasseyFergusonSA

Twitter: [Twitter.com/MF_EAME](https://twitter.com/MF_EAME)

Instagram: [Instagram.com/MasseyFergusonGlobal](https://www.instagram.com/MasseyFergusonGlobal)

YouTube: www.YouTube.com/MasseyFergusonGlobal

Blog: Blog.MasseyFerguson.com

AGCO South Africa Marketing

16 Pomona Road, Kempton Park, Gauteng, 1619



MASSEY FERGUSON® is a worldwide brand of AGCO.

© AGCO South Africa. 2021 | code*** | English